

macbond[®]

rivet tapes





Features

- Solvent-free, high-strength, rubber, pressure sensitive adhesive
- Available in 5.0 mil to 50 mil thickness
- Available in 0.5" to 11.5" adhesive widths
- Rolls are manufactured with ungummed edges for ease of application
- MTO & custom sizes will ship in 10-15 working days

Benefits

- Immediate bond to most surfaces from smooth to textured.
- Extremely durable and able to replace mechanical fasteners in many applications
- Thinner coatings are ideal for POP or craft assembly, thicker coatings are ideal for panel assembly, vibration dampening and moisture resistance.
- Acts as a third hand in many assembly applications.
- Ideal for use with metal, wood, polyethylene, polypropylene, glass and corrugated materials.

Markets & Applications

Appliance/White Goods 	Noise & Vibration Reduction
	Gaskets
	Packaging & Protection
Building & Construction 	Carpet & Flooring
	Insulation
	General Mounting
	Architectural Panels & Trim
Industrial & Fabrication 	Gaskets
	Seals
	Specialty Packaging
	Mounting
	Parts Assembly
Sign & Display 	Mounting Signs
	POP Displays
	Plaques
	Temporary Displays
Transportation & Recreational Vehicles 	Noise & Vibration Reduction
	Panel & Surround Assembly
	Trim Installation



We're Solid.
100% 

mactac[®]
Industrial Tapes and Adhesives

Mactac[®] is a pioneer in 100% solids adhesive technology bringing solutions that stick to the industrial tape and adhesive market since 1959.

macbond[®]

rivet tapes

Product Details

Part Number	Adhesive	Caliper (Mils) Adhesive	Adhesive Width	Liner Width	Roll Length	MOQ Rolls	Rolls/ Carton	Stock/ MTO
GS1001	GS Ultra High Tack	20	1.00"	1.50"	200'	8	8	Stock
GS1003	GS Ultra High Tack	20	.50"	1.00"	200'	12	12	Stock
GS1004	GS Ultra High Tack	35	.50" (RR)	2.00"	200'	6	6	Stock
GS1007	GS Ultra High Tack	35	1.00"	1.50"	200'	8	8	Stock
GS1013	GS Ultra High Tack	20	2.00"	3.00"	200'	4	4	Stock
GS1019	GS Ultra High Tack	35	0.75"	1.50"	200'	96	8	MTO
GS1023	GS Ultra High Tack	15	1.00"	1.50"	200'	96	8	MTO
GS2123200	GS Ultra High Tack	10	2.00"	3.00"	200'	36	4	MTO
GS2145-SC	GS Ultra High Tack	10	4.00"	5.00"	1350'	16	16*	Stock
GS2003	GS Ultra High Tack	5	0.75"	1.20"	900'	30	10	MTO
GS2004	GS Ultra High Tack	5	1.00"	1.50"	900'	24	8	MTO
GS2208	GS Ultra High Tack	15	4.00"	6.00"	400'	36	2	MTO
GS2313	GS Ultra High Tack	20	1.00"	1.20"	200'	120	10*	MTO
GS2603RR	GS Ultra High Tack	35	(2) @ .75" (RR)	3.00"	200'	48	4	MTO
GS2906	GS Ultra High Tack	50	2.00"	2.40"	150'	160	10	MTO

Performance Characteristics

Test	Units	Typical Values
Quick Tack	lbs/sq in	20+
Peel Adhesion	lbs/in	22+
Shear	hours to fail	300+
Application Temp	degrees F	+50
Service Temp	degrees F	0 to 180

Meets the following criteria:

- REACH and RoHS regulations
- Consumer Product Safety Improvement Act of 2008
- Toxics in Packaging
- Prop 65 Compliant
- Conflict Minerals

For additional Performance Guides on our GS Series tapes, please visit www.mactac.com.



972-224-9201

LGS Technologies | 2950 W Wintergreen Rd, Lancaster, TX 75134
email support@lgsco.com • www.lgstechologies.com

Mactac is ISO9001:2015 certified.
Mactac is a member of the following organizations:
Gasket Fabricators Association
Pressure Sensitive Tape Council

